

Water Coolers

Surprisingly Fast. In Cooling.





Water coolers are meant to cool water. But how fast, is what really matters. Especially in places like schools, colleges, offices and other corporate and commercial applications where the consumption of water is frequent and high. Which is why you need Blue Star Water Coolers.

Thanks to a powerful and rugged compressor, this latest range of coolers cool water surprisingly fast. Also, they come with an all-stainless steel body, making them more durable. And together with the power saving insulation and a comprehensive warranty, these coolers are complete value for money. What's more, even eco-friendly versions of these coolers are available. So you don't just get cold water, you also get a healthy environment, for years to come.

Blue Star is India's largest central airconditioning and commercial refrigeration company. With over seven decades of expertise in offering expert cooling solutions, Blue Star now brings to you water coolers with a wide range of features for every need.

Unmatched features of Blue Star Water Coolers

- Faster cooling
- Eco-friendly
- In situ power-saving PUF insulation
- Sturdy compressor and trouble free operation
- Silent operation
- Nationwide Blue Star network for prompt service
- SS Food grade SS tank & body





Other Highlights SDIx series:

- Stainless steel body:

 Your water cooler will look new and inviting even after years of use. No rusting, no corrosion
- Stainless steel tank:

 For safe drinking water, year after year
- Easy controls:

 The externally mounted thermostat makes it easy to set water temperature. No need to open service panels
- Speedy drainage:
 The extra large, stainless steel water tray prevents splashing and ensures fast drainage of water



NST series:

- Adjustable cold water thermostat
- Seam welded stainless steel tank
- Pre-coated outer body for better corrosion resistance
- Mechanically expanded condenser
- Front panel in stainless steel
- Sturdy moulded / flat / extended plastic legs
- Auto cut-out
- Riveted body assembly
- Over-load compressor protection



Technical Specifications for SDIx series

Model	Storage Capacity (Litres)	Nominal Cooling Capacity (Litres/hr)	No. of Faucets	Dimensions (mm)			Weight	Normal Demand**	Refrigerant	Current	Water Over Flow	Type of
				Width	Depth	Height	(kg)	(glasses per hr.)		(Amps)	(Connections)	Compressor
SDLx1210	12	10	1	400	400	670	19	50	R-134a	1.5	1/2 BSP	RECEIP
SDLx20	20	20	1	400	400	1060	30	100	R-134a	2.0	1/2 BSP	RECEIP
SDLx240	40	20	1	440	440	1150	34	100	R-134a	2.0	1/2 BSP	RECEIP
SDLx480	80	40	2	665	480	1210	47	200	R-134a	2.5	1/2 BSP	RECEIP
SDLx680	80	60	2	665	480	1210	47	300	R-22	3.0	1/2 BSP	RECEIP
SDLx8120	120	80	2	755	575	1240	62	400	R-22	3.8	1/2 BSP	RECEIP
SDLx150150	150	150	2	812	612	1210	66	750	R-22	8.1	1/2 BSP	ROTARY
SDLx100	380	170	4	1120	750	1500	95	850	R-22	8.0	1/2 BSP	ROTARY

^{*} SDIx 240, SDIx 480 & SDIx 15150 are also available with Plain & Cold options

- Cooling capacity as per comfort standards
- All models are suitable for operation on 230V/1 Ph/50 Hz AC supply
- Specifications, features and colours are subject to change without prior notice, due to continuous product development

Technical Specifications for NST series

Model	Storage Capacity (Litres)	Nominal Cooling (Litres/hr)	No. of Faucets	Dimensions (mm)			Weight	Normal Demand**	Refrigerant	Current	Water Over Flow	Type of
				Width	Depth	Height	(kg)	(glasses per hr.)	Who Tolke St	(Amps)	(Connections)	Compressor
NST15	20	20	1	400	400	1060	30	100	R-134a	2.0 A	1/2 BSP	RECEIP
NST480	80	60	2	665	480	1210	47	300	R-22	3.0 A	1/2 BSP	RECEIP
NST5120	120	80	2	755	575	1240	62	400	R-22	3.8 A	1/2 BSP	RECEIP
NST8150	150	170	2	812	612	1210	66	750	R-22	8.1 A	1/2 BSP	ROTARY

^{**} No. of glasses as per comfortable range of drinking water

- Cooling capacity as per comfort standards
- All models are suitable for operation on 230V/1 Ph/50 Hz AC supply
- Specifications, features and colours are subject to change without prior notice, due to continuous product development



Service and a se

For more information, please contact BLUE STAR LIMITED • Ahmedabad: 301 & 302. (3rd Floor), Abhishree Avenue, (Near) Nehru Circle, SM Road, Ambawadi, Ahmedabad - 380 015. Tel: (079) 40224000 • Bangaluru: Anjuman KAY A R R Tower, No - 28, Ward No 77, Mission Road, Bangalore - 560027. Tel: (080) 41854000 • Bhubaneshwar: 3A, Satya Nagar, 2nd Floor, Bhubaneshwar - 751 007. Tel: (0674) 2572403 / 2573670 • Chandigarh: Adarsh Mall, 4th Floor, Plot No. 50, Industrial & Business Park, Phase - Il, Chandigarh - 160 002. Tel: (0172) 5024000 • Chennal: No. 104, Old No. 46, Garuda buildings, Cathedral Road, Chennal - 600 086. Tel: (044) 42444000 • Ghaziabad: C 53A, Third Floor, Rajnagar District Center (RDC), Raj Nagar, Ghaziabad - 201001, Uttar Pradesh. Tel No: (0120) 2821400 • Goa: 210, 2nd Floor, Gera's Imperium I, Patto, Panjim, Goa - 403 001. Tel: (0832) 2438171/2437287 • Gurgaon: Block 2-A, DLF Corporate Park, DLF Qutab Enclave, Phase Ill, Mehrauli-Gurgaon Road, Gurgaon - 122 002. Tel: (0124) 4094100 • Guwahati: First Floor, Oasis Plaza, Dr. B. Barooah Road, Ulubari, Kamrup, Guwahati - 781 007. Tel: (0361) 2468496 • Indore: Shi Krishna Classic, First Floor, 139, Phadnis Colony, AB Road, Indore - 542 010. Tel: (0731) 4001211/4001311 • Jaipur: A-19, Ist Floor, Main Sahakar Path, Near Sahakar Bhavan, Jaipur - 302 001. Tel: (0141) 2744033-35 • Kochi: 2nd Floor, Millennium Plaza, MKK Nair Road, Alinchuvadu Junction, Kochi - 682 024. Tel: (0484) 4499000 • Kolkata: 7, Hare Street, Kolkata - 700 001. Tel: (033) 22134100 • Ludhiana: SCO 16-17, Feroze Gandhi Market, Fortune Chambers, 3rd Floor, Ludhiana - 141001 (Punjab), Tel: 0161 5001404 • Lucknow: 177/4, Faizabad Road, Lucknow - 226 007. Tel: (0522) 4034000 • Mumbai: Blue Star House, 9-A, Ghatkopar Link Road, Saki Naka, Mumbai - 400 072. Tel: (022) 66684100 • Nagpur: 219, Bajaj Nagar, 1st Floor, South Ambazari Road, Nagpur - 440 010. Tel: (0712) 2249000 / 6624000 • Pune: 201/A, Nityanand Complex, 1st Floor, 247/A, Bund Garden Road, Pune - 411 001. Tel: (020) 41044000 / 261693

^{**} No. of glasses as per comfortable range of drinking water